

IBR-5 Bronze Pop-Type Safety Valve Screwed, Open Discharge (IBR Approved)

Product Description

HSN 84814000

Product : 'SANT' Bronze Safety Valve
 Body Material cum Standard : Bronze IBR 282(a)(iv) Gr.B
 Description : Pop-Type open discharge
 Type of Seat : Integral
 Type of Disc : Renewable Disc
 Trim : Cu-Alloy
 End Details : Inlet screwed male BSP Taper threads to BS 21

Testing & Certification

Body Test Pressure : 500 Psig.Hyd.
 Working Pressure : Max.BOP 250 Psig.(17.58Kg/cm²)
 Maximum Working Temperature: 225°C (435°F)

Note : Please advice set pressure while placing order

Test Certificate in Form III-C as per IBR is furnished with every supply.

Application

Gas	Steam
-----	-------




Materials of Construction

Components	Materials	Specifications
Body, Spring Chamber, Valve Disc, Blow-down Ring, Spring Discs & Adjusting Screw	Bronze	IBR 282(a)(iv) Gr.B
Spindle, Check Nuts & Screws	Forged Brass	IS:6912 FLB
Spring	Spring Steel	IBR 307 to 314
Cap	Aluminium Casting	—
Easing Lever	Mild Steel	—

Dimensions (in mm)

Nominal Size	Nominal Size (Inches)	ØA (Inches)	B (Inches)	H (Approx.)
15	1/2	1/2	3/4	290
20	3/4	3/4	1	325
25	1	1	1.1/4	325
40	1.1/2	1.1/2	2	420
50	2	2	2.1/2	460
			BSP (T)	



Notes

- Product images are for illustration purposes only. Actual product may vary.
- Actual dimensions may change over time, due to continual design improvements. Please confirm before placing order.