

CR-19B Cast Iron Wedge Sluice Valve Flanged, OS & Yoke Type Rising Stem, PN16

Product Description

HSN 84818030

Product : 'SANT' Cast Iron Wedge Gate Sluice Valve
 Product Standard : Face To Face as per IS:14846
 Pressure / Class / Rating : PN 16 PD Type
 Body Material cum Standard : Cast Iron IS:210 Gr.FG200
 Description : Bolted Bonnet, Outside Screw & Yoke Type Rising Stem
 Type of Seat : Renewable seat
 Type of Disc : Solid wedge
 Trim : Cu-Alloy Rings, Stem SS AISI-410
 Gland Packing : Rubber
 End Details : Flanges as per IS:1538 FF drilled



Testing & Certification

Body Test Pressure : 2.4MPa (Hyd.)
 Seat Test Pressure : 1.6MPa (Hyd.)

Our Works' Test Certificate is furnished with every supply.

Application


Water

Materials of Construction

Components	Materials	Specifications
Body, Handwheel, Wedge, Bonnet, Gland	Cast Iron	IS:210 Gr.FG200
Handwheel Nut, Yoke Sleeve Nut, Stem, Gland, Back Seat Bush	Stainless Steel	AISI-410
Studs & Nuts.	M.S	—
Gland Packing	Rubber	IS:638 Type B
Gasket	Rubber	IS:638 Type B
Body Seat Ring, Wedge Ring	Leaded Tin Bronze	IS:318 Gr.LTB2
Yoke Sleeve	Bronze	—
Bolts / Nuts	Mild Steel	—

Dimensions (in mm)

Nominal Size	Nominal Size (Inches)	F	H (Approx.)	ØW (Approx.)
50	2	178±2	315	178
65	2.1/2	190±2	365	178
80	3	203±2	410	210
100	4	229±2	475	254
125	5	254±2	535	254
150	6	267±2	620	305
200	8	292±2	795	400
250	10	330±3	930	450
300	12	356±3	1100	500



Notes

1. Product images are for illustration purposes only. Actual product may vary.